

# TY170-GS12XB

17" Intel® Core™ 12th i3/i5/i7 Processor  
Industrial Panel PC



## Features:

- 17" Intel® Processor Core/N-series Alder Lake 12th Gen i3/i5/i7 & N97/N100
- Industrial display screen, multi point capacitive touch screen
- 2\*DDR4 8GB (up to 32GB supported)
- 4\*USB/1\*RS232/485/422,DB9,Jumper switching
- 1\*HD/1\*VGA/2\*RJ45/2\*Audio
- Fanless design

## Specifications:

### System Hardware

CPU	Intel® Processor Core™ /N-series Alder Lake 12th Gen i3/i5/i7 & N97/N100	Memory	8GB (optional 16/32GB)
Watchdog	0-255 seconds/grading implemented through system software	Storage	128GB SSD (optional 256/512GB)

### Display

LCD Type	17"	Luminance	300 cd/m <sup>2</sup>
Max. Resolution	1280*1024	Contrast Ratio	1000: 1
Touchscreen Type	17" Multi point capacitive touch screen		

### OS

OS	Windows 10、 Ubuntu
----	--------------------

### I/O Ports

USB	2*USB3.2, 2*USB2.0(optional USB3.0)	Audio	1*Line out, 1*MIC in
Serial port	1*RS232/485/422, DB9, Jumper switching (optional 3*RS232/485/422, DB9, Jumper switching)	Video	1*HDMI, 1*VGA(optional 1*HDMI/DP/DVI)
LAN	2*RJ45 (optional Realtek)	Expansion Slot	Optional dual band WIFI/BT, optional 4G/5G communication
		SIM Card	Optional with 4G/5G

## Power

Power Input Standard 12V/5A Phoenix terminal(Optional with electric self starting and 9-36V wide voltage input)

## Environment

Vibration Protection	5-17Hz/1.0mm amplitude; 17-200Hz/1.0g acceleration	Operating Temp.	-10°C~60°C, Surface air flow
Shock Protection	10g acceleration, 11ms cycle	Storage Temp.	-20°C~70°C
Reliability	MTBF ≥ 30000h; MTTR ≤ 0.5h	Humidity	95% @ 40°C, no condensation
		IP Rating	Front panel IP65

## Mechanical

Dimension (WxHxD)	398mm*323.6mm*53.2mm	Material	All metal fanless design
Weight	4.6kg/5.1kg(N.W./G.W.)	Mounting	VESA Installation: 75*75mm/100*100mm
Color	Black		Embedded Installation: 384mm*314mm

## Dimensions:

